



Motor

Izlazna snaga	3.0 kW
Zapremina cilindra	50.1 cm³
Broj okretaja pri maksimalnoj snazi	10200 o/min
Brzina praznog hoda	2800 o/min
Moment, max.	3.15 Nm
Moment, maks. na rpm	7800 o/min
Brzina angažiranja spojke	3900 o/min
Potrošnja goriva	432 g/kWh
Potrošnja goriva	1.3 kg/h
Svjećica	NGK CMR6H
Zazor elektroda	0.5 mm
Zazor bobine	0.3 mm
Tip uljne pumpe	Podesiv protok, nema toka u praznom hodu
Emisije plinova (CO2 EU V)	813 g/kWh¹⁾



Dimenzije

Težina (bez rezne opreme)	5.3 kg
---------------------------	---------------



Maziva

Tip podmazivanja	Husqvarna 2-taktno ili ekvivalentno na 50:1
Zapremina rezervoara ulja	0.32 l



Oprema

Dužina vodilice	15 in
Tip lanca	SP33G
Tip lančanika	Obruč 7
Tip vodilice	Mali
Preporučena dužina vodilice, min-maks	13-20 in



Zvuk i buka

Nivo zvuka, LWA	117 dB(A)
Mjerenje razine buke	115 dB(A)
Jačina zvuka u uhu operatera	107 dB(A)



Vibracije

Ekvivalentna razina vibracija (AHV, eq) prednja / zadnja ručka	3.3 m/s²
Ekvivalentna razina vibracija (AHV, eq) prednja / zadnja ručka	4.9 m/s²